

Product Datasheet

CF4.6 H1 (Overprintable Cold Foils)

Main Characteristics	Over-printable with both conventional and most of UV inks
	Fine definition with consistent release
	Excellent board coverage with high glossy
	High operating speed and well suitable for the listed UV-Adhesive
Recommended Applications	Applicable on suitably modified reel-to-reel label presses with cold foil unit, ex. Gallus, Mark Andy, Nilpeter....presses
	Applicable on a wide range of substrate such as non-absorbent surface papers and all types of label stock, ex. PP, PE.....
Operating Hints	UV adhesive weight: Label films:3.0~6.0 g/m2; Non-absorbent paper:6.0~8.0g/m2
	Running speed: 40M – 120M /per minute
	UV lamp output: Higher 180W/cm (450 W/inch)
	Ensure that you use an appropriate adhesive, ex. Flint XSYS、Paragon、JS、Northwest、Select、Sun Chemical...cold foil UV adhesives.
	Ensure the hardness of nip roller is between 85 to 90 shore A hardness.
Standard roll format	Various roll formats are available to order - please enquire.
Shelf life and Storage	Use <i>Univacco</i> product within one year after production
	Keep <i>Univacco</i> product in its original package and away from high temperature, sunlight exposure and humidity.
	Master rolls are best stored vertically. If store horizontally, please keep the original boxes and packages for your storage. Jumbo rolls should be suspended horizontally and avoid direct contact with the ground or other items.
Issue Number	A.3
Date	2014/03/10

All UNIVACCO products have been developed for a particular range of applications. However, experience shows that substrates, printing equipment and operating conditions can vary, and users of our products are urged to verify, by means of test printing, that particular grades are appropriate for their specific applications. For this purpose, test samples are available on request. If you need help, UNIVACCO will be happy to assist. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.