

# Product Datasheet

<b>777</b>	
<b>Main characteristics</b>	<ul style="list-style-type: none"> <li>* Good adhesion and fine definition with consistent release</li> <li>* Good abrasion and scratch resistance.</li> <li>* Suitable for UV varnished and coated papers</li> </ul>
<b>Substrate</b>	PET/OPP laminated papers, plain paper and board, printed paper and other various papers.
<b>Recommended applications</b>	<ul style="list-style-type: none"> <li>* Suitable for printing jobs with design of extremely fine definition</li> <li>* Wine and spirit boxes, labels, cigarette packages, cosmetic packaging boxes, greeting cards other applications in graphics industry.</li> </ul>
<b>Relevant equipment</b>	Vertical, Clam-shell and Cylinder machines
<b>Operating hints</b>	<ul style="list-style-type: none"> <li>* Vertical, platen and clam-shell machines: 105°C - 135°C</li> <li>* Cylinder machines: 130°C - 160°C</li> <li>* Find the best combination by adjusting temperature, dwell time and pressure to achieve the best stamping effects.</li> <li>* Ensure that the Die surface is clean.</li> <li>* Ensure that ink on the substrate (if any) is dry before stamping.</li> </ul>
<b>Availability</b>	Gold and Silver
<b>Specification</b>	Standard roll : 12μ × 640mm × 120m in 1"inch core Jumbo roll : 12μ × 1280mm × 3000M in 3"inch core Other roll formats are available to order - please enquire.
<b>Order Instruction</b>	MOQ for Gold/Silver : 200 standard rolls or Jumbo roll 12000M
<b>Shelf life and storage</b>	<ol style="list-style-type: none"> <li>1. Use Univacco product within one year after production</li> <li>2. Keep product in its original package and away from high temperature, sunlight exposure and humidity.</li> <li>3. Master rolls are best stored vertically. If store horizontally, please keep the original boxes and packages for your storage.</li> <li>4. Jumbo rolls should be suspended horizontally and avoid direct contact with the ground or other items.</li> </ol>
<b>Issue Number</b>	<b>A.2</b>
<b>Date</b>	<b>2015/06/17</b>

All UNIVACCO products have been developed for a particular range of applications. However, experience shows that substrates, printing equipment and operating conditions can vary, and users of our products are urged to verify, by means of test printing, that particular grades are appropriate for their specific applications. For this purpose, test samples are available on request. If you need help, UNIVACCO will be happy to assist. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.